

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 2 Revision Date 22.01.2018

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifiers

Product name : Sudan III Alcoholic 0.5% solution

Product Number : 5701

Brand : Better Equipped

Index-No. : 603-002-00-5

REACH No. : A registration number is not available for this substance as the substance or its uses are exempted from registration or the annual tonnage does not require a registration.

CAS-No. : 64-17-5

This substance is a mixture and the hazardous components information used for this section.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

Uses advised against : Not for sale to the general public

### 1.3 Details of the supplier of the safety data sheet

Company : Better Equipped,  
Wrenbury Business Park,  
Wrenbury Road,  
Wrenbury,  
Nantwich, Cheshire,  
CW5 8EB, UK

Telephone +44 (0) 800 9707142

Fax +44 (0) 800 066 4443

E-mail address [sales@betterequipped.co.uk](mailto:sales@betterequipped.co.uk)

### 1.4 Emergency telephone number

Emergency Phone # +44 (0)1270 781238

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225  
Eye irritation (Category 2), H319  
Spec target organ tox - single, (category 2), (STOT SE 2).

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 Label elements

#### Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.

Precautionary statement(s) P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378 P403 + P235	In case of fire: Use dry powder or dry sand to extinguish. Store in a well-ventilated place. Keep cool.
Supplemental Hazard Statements	none

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Synonyms	:	Ethyl alcohol
Formula	:	C <sub>2</sub> H <sub>6</sub> O
Molecular weight	:	46.07 g/mol
CAS-No.	:	64-17-5
EC-No.	:	200-578-6
Index-No.	:	603-002-00-5

#### Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
<b>Ethanol</b>		
CAS-No. 64-17-5 EC-No. 200-578-6 Index-No. 603-002-00-5	Flam. Liq. 2; Eye Irrit. 2; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	>90%<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical or carbon dioxide.

#### Unsuitable extinguishing media

Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

### 5.4 Further information

Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### - 6.1.1 For non-emergency personnel

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### - 6.1.2 For emergency responders

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.1.2 Advice on general occupational hygiene:

- No smoking.
- Do not eat or drink.
- Wash hands after use.
- Remove contaminated clothing.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hygroscopic.

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value/Form of exposure	Control parameters	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	UK. EH40 WEL - Workplace Exposure Limits
	Remarks	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used		

#### 8.1.2 Information on currently recommended monitoring procedures

For currently recommended monitoring procedures, see HSE series 'Methods for the Determination of Hazardous Substances' (MDHS)

#### 8.1.3 The relevant DNELs and PNECs for the substance/s for the exposure scenarios:

DNEL's. The derived no- or minimum effect level (DN(M)EL) is the level of exposure above which a human should not be exposed to a substance. Please note that when more than one summary is provided, DN(M)EL values may refer to constituents of the substance and not to the substance as a whole.

##### Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	343mg/kg BW/d
Workers	Ingestion	Long-term systemic effects	343mg/kg BW/d
Workers	Inhalation	Acute local effects	1900 mg/m <sup>3</sup>

PNEC's. The Predicted No-Effect Concentration (PNEC) value is the concentration of a substance below which adverse effects in the environment are not expected to occur. Please note that when more than one summary is provided, PNEC values may refer to constituents of the substance and not to the substance as a whole.

##### Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.63 mg/kg
Marine water	0.79 mg/l
Fresh water	0.96 mg/l
Fresh water sediment	3.6 mg/l
Sewage treatment plant	580 mg/l

### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Use Local exhaust ventilation (LEV).

#### Personal protective equipment

##### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

#### Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

#### Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 38 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, Colour: Red
b)	Odour	Ethanol like
c)	Odour Threshold	No data available
d)	pH	pH 6-8 at 20 °C
e)	Melting point/freezing point	Melting point/range: -114 °C
f)	Initial boiling point and boiling range	78 °C
g)	Flash point	23 °C - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 19 %(V) Lower explosion limit: 3.3 %(V)
k)	Vapour pressure	59.5 hPa at 20.0 °C
l)	Vapour density	No data available

m)	Relative density	0.789 g/mL at 25 °C
n)	Water solubility	completely soluble
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available

## 9.2 Other safety information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None known based on the data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

None under normal processing

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Alkali metals, Oxidizing agents, Peroxides

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - 10,470 mg/kg  
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l  
(OECD Test Guideline 403)

LC50 Inhalation - Rat - 4 h - 30,000 mg/l

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation  
(OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.  
(OECD Test Guideline 405)

#### Respiratory or skin sensitisation

Sensitisation test:

Result: negative

Remarks: (IUCLID)

#### Germ cell mutagenicity

Ames test

Salmonella typhimurium  
Result: negative

In vitro mammalian cell gene mutation test  
Mouse lymphoma test  
Result: negative

OECD Test Guideline 478  
Mouse - male

### **Carcinogenicity**

Carcinogenicity - Mouse - Oral

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### **Reproductive toxicity**

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependence.

### **Specific target organ toxicity - single exposure**

No data available

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

### **Additional Information**

RTECS: KQ6300000

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish                      flow-through test LC50 - Pimephales promelas (fathead minnow) - 15.3 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates                      LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h

NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d

Toxicity to algae                      EC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h  
(OECD Test Guideline 201)

**12.2 Persistence and degradability**

Biodegradability                      aerobic - Exposure time 15 d  
Result: 95 % - Readily biodegradable.  
(OECD Test Guideline 301E)

**12.3 Bioaccumulative potential**

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

No data available

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Unused product may be returned and reused, in addition to disposal.

**Contaminated packaging**

Dispose of as unused product.

**SECTION 14: Transport information**

**14.1 UN number**

ADR/RID: 1170                              IMDG: 1170                              IATA: 1170

**14.2 UN proper shipping name**

ADR/RID: ETHANOL  
IMDG: ETHANOL  
IATA: Ethanol

**14.3 Transport hazard class(es)**

ADR/RID: 3                                      IMDG: 3                                      IATA: 3

**14.4 Packaging group**

ADR/RID: III                                      IMDG: III                                      IATA: III

**14.5 Environmental hazards**

ADR/RID: no                                      IMDG Marine pollutant: no                                      IATA: no

**14.6 Special precautions for user**

No data available

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

N/A

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.



## 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

---

### SECTION 16: Other information

#### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

#### Revisions made since previous version of data sheet:

The following sections of this data sheet have been updated:

1.1, 1.2, 4.1, 5.1, 6.1, 7.1, 8.1, 8.2, 11, 12, 13, 14.7, 16

We strongly recommend reading the entire data sheet for this chemical in preparation ahead of use.

#### Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Better Equipped and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

---

## Annex: Exposure scenario

### Identified uses:

#### Use: Used as chemical intermediate

<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>SU 3, SU9:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
<b>PC19:</b> Intermediate
<b>PROC1:</b> Use in closed process, no likelihood of exposure <b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure <b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC4:</b> Use in batch and other process (synthesis) where opportunity for exposure arises <b>PROC8b:</b> Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
<b>ERC1, ERC4, ERC6a:</b> Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

#### Use: Formulation of preparations

<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>SU 10, SU 3:</b> Formulation [mixing] of preparations and/ or re-packaging (excluding alloys), Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC5:</b> Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) <b>PROC8a:</b> Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities <b>PROC8b:</b> Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities <b>PROC9:</b> Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
<b>ERC2:</b> Formulation of preparations

#### Use: Industrial use of processing aids in processes and products, not becoming part of articles

<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>SU 3, SU9:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
<b>PROC1:</b> Use in closed process, no likelihood of exposure <b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure <b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC4:</b> Use in batch and other process (synthesis) where opportunity for exposure arises <b>PROC8b:</b> Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
<b>ERC1, ERC4, ERC6a:</b> Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

#### Use: Used as laboratory reagent

<b>SU 22:</b> Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
<b>SU 3, SU 22:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
<b>PC21:</b> Laboratory chemicals
<b>PROC15:</b> Use as laboratory reagent
<b>ERC2, ERC4, ERC8a:</b> Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

#### Use: Surface treatment

<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
---

<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>PROC10:</b> Roller application or brushing
<b>PROC13:</b> Treatment of articles by dipping and pouring
<b>ERC4:</b> Industrial use of processing aids in processes and products, not becoming part of articles

### 1. Short title of Exposure Scenario: Used as chemical intermediate

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC19
Process categories	: PROC1, PROC2, PROC3, PROC4, PROC8b
Environmental Release Categories	: ERC1, ERC4, ERC6a:

### 2. Exposure scenario

#### 2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

##### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PC19

##### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).  
Physical Form (at time of use) : Liquid substance

##### Frequency and duration of use

Application duration : > 4 h  
Frequency of use : 240 days/year

##### Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

##### Technical conditions and measures

Provide adequate ventilation., Good work practice required.

##### Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

##### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

### 3. Exposure estimation and reference to its source

#### Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

#### Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	0.0192083 mg/m <sup>3</sup>	0
PROC2	ECETOC TRA	Without Local	Inhalation	19.2083333	0.02

		Exhaust Ventilation		mg/m <sup>3</sup>	
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	1.3714 mg/kg BW/d	0.004
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	48.0208333 mg/m <sup>3</sup>	0.051
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	38.4166667 mg/m <sup>3</sup>	0.04
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101

\*Risk characterisation ratio

#### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

#### 1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : SU 3  
 Sectors of end-use : SU 10, SU 3  
 Process categories : PROC3, PROC5, PROC8a, PROC8b, PROC9  
 Environmental Release Categories : ERC2:

#### 2. Exposure scenario

##### 2.1 Contributing scenario controlling environmental exposure for: ERC2

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

##### 2.2 Contributing scenario controlling worker exposure for: PROC3, PROC5, PROC8a, PROC8b, PROC9

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Liquid substance

###### Frequency and duration of use

Application duration : > 4 h  
 Frequency of use : 240 days/year

###### Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

###### Technical conditions and measures

Provide adequate ventilation., Good work practice required.

### Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

## 3. Exposure estimation and reference to its source

### Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

### Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	48.0208333 mg/m <sup>3</sup>	0.051
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001
PROC5	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.7143 mg/kg BW/d	0.04
PROC5	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101
PROC8a	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.7143 mg/kg BW/d	0.04
PROC8a	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02
PROC9	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101

\*Risk characterisation ratio

## 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

## 1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Process categories	: PROC1, PROC2, PROC3, PROC4, PROC8b
Environmental Release Categories	: ERC1, ERC4, ERC6a:

## 2. Exposure scenario

### 2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

#### Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
---	--

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b

#### Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	: Liquid substance

#### Frequency and duration of use

Application duration	: > 4 h
Frequency of use	: 240 days/year

#### Other operational conditions affecting workers exposure

Outdoor / Indoor	: Indoor
------------------	----------

#### Technical conditions and measures

Provide adequate ventilation., Good work practice required.

#### Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

## 3. Exposure estimation and reference to its source

### Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

### Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	0.0192083 mg/m <sup>3</sup>	0
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	19.2083333 mg/m <sup>3</sup>	0.02
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	1.3714 mg/kg BW/d	0.004

PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	48.0208333 mg/m <sup>3</sup>	0.051
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	38.4166667 mg/m <sup>3</sup>	0.04
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101
PROC8b	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	6.8571 mg/kg BW/d	0.02

\*Risk characterisation ratio

#### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

#### 1. Short title of Exposure Scenario: Used as laboratory reagent

Main User Groups : SU 22  
 Sectors of end-use : SU 3, SU 22  
 Chemical product category : PC21  
 Process categories : PROC15  
 Environmental Release Categories : ERC2, ERC4, ERC8a:

#### 2. Exposure scenario

##### 2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4, ERC8a

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

##### 2.2 Contributing scenario controlling worker exposure for: PROC15, PC21

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Liquid substance

###### Frequency and duration of use

Application duration : 1 - 4 h

Frequency of use : 240 days/year

###### Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

###### Technical conditions and measures

Provide adequate ventilation., Good work practice required.

###### Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

## Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

### 3. Exposure estimation and reference to its source

#### Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

#### Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	19.2083333 mg/m <sup>3</sup>	0.02
PROC15	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.001

\*Risk characterisation ratio

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

#### 1. Short title of Exposure Scenario: Surface treatment

Main User Groups : **SU 3**  
 Sectors of end-use : **SU 3**  
 Process categories : **PROC10, PROC13**  
 Environmental Release Categories : **ERC4:**

#### 2. Exposure scenario

##### 2.1 Contributing scenario controlling environmental exposure for: ERC4

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

##### 2.2 Contributing scenario controlling worker exposure for: PROC10, PROC13

###### Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).  
 Physical Form (at time of use) : Liquid substance

###### Frequency and duration of use

Application duration : > 4 h  
 Frequency of use : 240 days/year

###### Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

###### Technical conditions and measures

Provide adequate ventilation., Good work practice required.

###### Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.



### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

### 3. Exposure estimation and reference to its source

#### Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

#### Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC10	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101
PROC10	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	27.4286 mg/kg BW/d	0.08
PROC13	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	13.7143 mg/kg BW/d	0.04
PROC13	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	96.0416667 mg/m <sup>3</sup>	0.101

\*Risk characterisation ratio

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).